



Contact arrangements - high voltage 5500 subsea connectors

Face view of pin connectors shown, insert arrangement designators are followed by contact sizes and suggested wire gauges




1503

- 3 X 1/16" contacts
#18 AWG wires
1000V, 2000V




1603

- 3 X 1/16" contacts
#16 AWG wires
1000V, 2000V




2004

- 3 X 1/8" contacts
■ 1 X 5/32 contact
#14 AWG wires
1000V, 2000V, 3000V




2013

- 13 X 1/16" contacts
#18 AWG wires
1000V




2403

- 3 X 3/32" contacts
#14 AWG wires
1000V, 2000V, 3000V




2410

- 10 X 3/32" contacts
#16 AWG wires
1000V, 2000V




2420

- 20 X 1/16" contacts
#18 AWG wires
1000V




3203

- 3 X 3/16" contacts
#8 AWG wires
1000V, 2000V, 3000V, 5000V




3204

- 4 X 3/16" contacts
#8 AWG wires
1000V, 2000V, 3000V, 5000V




3210

- 10 X 5/32" contacts
#14 AWG wires
1000V, 2000V, 3000V




3212

- 12 X 1/8" contacts
#14 AWG wires
1000V, 2000V, 3000V



3224

- 24 X 1/16" contacts
#18 AWG wires
1000V



3239

- 39 X 1/16" contacts
#18 AWG wires
1000V